ACACIA BUTCHER BLOCK



CONGRATULATIONS on purchasing a Sparrow Peak Acacia Butcher Block, the best valued butcher block product on the market today! With the proper treatment it will look great for years to come.

Acacia is known for its beautiful contrast of heartwood and sapwood. Sparrow Peak Acacia comes in multiple color choices including Natural or pre-stained in one of four colors – Honey, Spice, Espresso or Ebony. Acacia wood is a product of nature and will display characteristics that are unique to each piece.

CARE INSTRUCTIONS:

- This butcher block <u>MUST</u> be sealed or finished on all surfaces within <u>48 HOURS</u> of removing shrink wrap.
- This wood top can be cut to size with standard wood working tools.
- For tips on staining and color matching, please visit <u>www.sparrowpeak.com/acacia</u>
- When sealing with mineral oil or conditioner, apply an even, liberal coat on all surfaces and edges. Let absorb for approximately 20 minutes then wipe off any excess with clean towel. Re-apply as necessary. General use and cleaning of this top will require frequent application of conditioner or mineral oil to extend the life of the product. Frequency may range from every few weeks to every few months.
- There are several other options for finishing your butcher block. See a Lowe's paint sales specialist for more information.
- If finished properly, this surface can be used for food prep; however, we recommend that a cutting board or mat be used to preserve the life and look of the block.
- Always clean your work top surface before and after each use.

WARRANTY:

- This product comes with a 90 day limited warranty.
- It can be exchanged or refunded if the product has delaminating staves, joint separation, or other damages because of faulty fabrication.
- The product warranty will not cover product damage due to improper storing, handling, alteration, or installation.
- Any damage due to transportation must be reported immediately. If upon receipt the packaging appears to be damaged please unpack immediately and check for potential damage.
- The butcher block must be sealed or finished on all surfaces within 48 hours of removing shrink wrap.